

Intercambiabilità componenti-Interchangeability of parts

TIPO	Corpo supporto			Albero pompa					Cuscinetti				Tenuta sull'albero		
	1	2	3	I	II	III	IV	V	6207 Z 6306 Z	6207 Z 3306	6309 Z 3309	6311 Z 3311	Ø 32	Ø 40	Ø 50
RN,RN4 32-125	•			•					•				•		
RN,RN4 32-160	•				•				•				•		
RN,RN4 32-200	•				•				•				•		
RN,RN4 40-125	•				•				•				•		
RN,RN4 40-160	•				•				•				•		
RN,RN4 40-200C	•				•				•				•		
RN,RN4 40-200A-AR-B	•					•				•			•		
RN,RN4 40-250	•					•				•			•		
RN,RN4 50-125	•				•				•				•		
RN,RN4 50-160	•					•				•			•		
RN,RN4 50-200	•					•				•			•		
RN,RN4 50-250	•					•				•			•		
RN,RN4 65-125E	•				•				•				•		
RN,RN4 65-125A-C	•					•				•			•		
RN,RN4 65-160	•					•				•			•		
RN,RN4 65-200	•					•				•			•		
RN,RN4 65-250		•					•				•			•	
RN4 65-315		•					•				•			•	
RN,RN4 80-160	•					•				•			•		
RN,RN4 80-200		•					•				•			•	
RN,RN4 80-250		•					•				•			•	
RN4 80-315		•					•				•			•	
RN4 80-400			•					•				•			•
RN,RN4 100-200		•					•				•			•	
RN,RN4 100-250		•					•				•			•	
RN4 100-315		•					•				•			•	
RN4 100-400			•					•				•			•
RN4 125-250		•					•				•			•	
RN4 125-315			•					•				•			•
RN4 125-400			•					•				•			•
RN4 150-315			•					•				•			•
RN4 150-400			•					•				•			•

Velocità di rotazione massima ammessa- Maximum permissible rotation speed

3600 1/min			3000 1/min			1800 1/min		
32-125	32-160	32-200						
40-125	40-160	40-200			40-250			
50-125	50-160	50-200			50-250			
65-125	65-160			65-200	65-250		65-315	
		80-200	80-160		80-250		80-315	80-400
		100-200			100-250		100-315	100-400
						125-250	125-315	125-400
							150-315	150-400

I dati indicati non sono impegnativi e possono cambiare con le condizioni di lavoro
Technical data are indicative and they can change according to pump work